

# Bona Extender

PART OF THE BONA ADDITIVE+ RANGE

**Increases open time in warm or dry conditions.**



Bona Extender is an additive that improves levelling and prolongs the open time of Bona waterborne finishes, primers and paints.

It is designed for use when indoor humidity is low and/or the room temperature is higher than normal. Bona Extender extends open time, enabling contractors to work at a steady, comfortable pace with enhanced control. This minimises stress during application and ensures a more consistent, professional result.

- Facilitates application in warm/dry climates
- For wood and resilient floors
- Prolongs open time
- Improves levelling properties

# Bona Extender

PART OF THE BONA ADDITIVE+ RANGE

**Increases open time in warm or dry conditions.**

## TECHNICAL DATA

<b>Mixing ratio:</b>	Finishes & primers: max 4 % (one bottle per 5 L), Line Paint: max 10 %.
<b>Fire risk:</b>	Non-flammable.
<b>Safety:</b>	Unclassified.
<b>Shelf life:</b>	2 years from date of production in unopened original container.
<b>Storage/Transport:</b>	The temperature must not fall below +5° C or exceed +30° C during storage or transport.
<b>Disposal:</b>	Containers with a minimal amount of dried material may be recycled. Liquid waste must be disposed of at an approved waste disposal facility - do not pour down drains or sewers. Follow all local waste regulations.
<b>Pack size:</b>	200 ml.

*Additional detailed information is noted in the appropriate Safety Data Sheet.*

## APPLICATION

### **Bona Waterborne Finishes & Primers, Bona Pure Colour & Bona SuperSport Zone Paint**

Add maximum 4% (200 ml to 5 L) Bona Extender to the finish and shake thoroughly.

Apply finish mixed with Bona Extender as normal, according to the instructions on each product's technical data sheet.

### **Bona SuperSport Line Paint**

Add up to 10% Bona Extender to the paint and stir thoroughly before use. Use as normal.

## IMPORTANT!

When using Extender with 2-component products, Extender must be added only after the finish and Hardener have been thoroughly mixed.

# Bona Extender

PART OF THE BONA ADDITIVE+ RANGE

**Increases open time in warm or dry conditions.**

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.