



Bona SuperSport Cleaner

SPORTS FLOOR MAINTENANCE

Daily cleaning of wood & resilient sports flooring.



Bona SuperSport Cleaner is a concentrated slightly alkaline detergent specifically designed for frequent cleaning of indoor sports surfaces. Bona SuperSport Cleaner is gentle on the surface yet will effectively remove grease and grime, whilst leaving no residual film on the surface. Its low foaming formula is suitable for auto scrubber as well as manual application.

- Safe for use on both wood & resilient surfaces
- Leaves no slippery residue
- Low foaming

1.05.2025

This data sheet replaces all previous versions.

Please check bona.com.au to ensure that you have the latest version



Bona SuperSport Cleaner

SPORTS FLOOR MAINTENANCE

Daily cleaning of wood & resilient sports flooring.

TECHNICAL DATA

Product type:	Surfactant solution
pH-value:	approx. 11 (concentrate) approx. 10 (diluted working solution)
Dilution:	Normal cleaning: 50 ml cleaner to 5 litres water (1:100) Heavily soiled floors: 100 ml cleaner to 5 litres water (1:50)
Safety:	Unclassified, see Safety Data Sheet for more information.
Shelf life:	2 years from date of production, in unopened original container
Storage/transport:	Protect from freezing.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size	5 litres

DIRECTIONS FOR USE

Routine Maintenance

1. Dry clean the floor with a Bona Microfiber Dusting pad, scissor mop, etc. to remove all loose dirt.
2. Dilute Bona SuperSport Cleaner with cold water for routine cleaning, 50 ml to 5 L. Clean the floor with the solution and let the surface dry sufficiently before resuming traffic.
3. For heavy contamination, use a dilution of 100 ml to 5 L water.

Note: On wood floors use as little liquid as possible as excess amounts may cause swelling and permanent damage to the flooring.

Large areas

1. For larger areas Bona SuperSport Cleaner is suitable for use in an auto scrubber, such as a Bona PowerScrubber, with white brushes. Use a dilution of 100 ml to 10 L cold water for routine maintenance or 200 ml to 10 L water in the case of heavier soiling.
2. Always fill the tank with clean water prior to use.
3. Run the machine along, never across, parquet boards.
4. Water loss from the machine must not exceed 1 L / 100 m². Test by adding 10 litres of water to the tank and check the remaining water after 100 m², 9 litres should remain in the return tank.
5. Water should be removed promptly, make sure not to leave puddles when turning the machine.
6. Keep the suction strip clean and in good condition. Replace annually or if the machine is leaving too much water on the floor.
7. Do not use aggressive brushes or pads on the surface. Aggressive pads / brushes may scratch and wear the surface. The milder the pad/brush, the less the wear.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturers and the provisions of relevant standards.

1.05.2025

This data sheet replaces all previous versions.

Please check bona.com.au to ensure that you have the latest version